

## 1140 Serial Impact Printer



The Tally Dascom 1140, is a 9 pin, 80 column serial dot matrix printer with a USB interface as standard. Compact in size, the 1140 is perfect for industrial environments and front and back office applications where space is limited.

With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

### Highlights at a glance:

- Compact 9-pin narrow carriage printer
- Up to 400 characters per second
- Ideal for front and back office applications
- Variety of interfaces
- Long life ribbon
- Small footprint

In addition to these applications, the 1140 is also well suited to measurement and control systems. Among the lowest priced matrix printers available today, the 1140 also offers a long life ribbon giving this printer very low running costs.

For draft printing it's considerably less expensive operating costs make it a viable alternative to low end inkjet printers.

### Configurations Available:

Part Number	Description
28830504 099007	1140 Printer, 9 pin, 80 Col - 110/240v, USB Ribbon, Tally Dascom 1140

## 1140

<b>Print Speed</b>	400 cps (Fastest Draft); 300 cps (Draft), 75 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 144 x 240 dpi
<b>Throughput</b>	290 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 8 lpi
<b>Print Head Life</b>	400 million strokes
<b>Memory</b>	up to 256 kB
<b>Standard Connectivity</b>	USB 2.0
<b>Optional Connectivity</b>	Parallel IEEE 1284, Serial RS-232C, Ethernet (10/100)
<b>Standard Emulation</b>	IBM ProPrinter 2380 Plus, Epson ESCP/2
<b>Fonts</b>	Draft, Quadrato, Courier, HS Draft, OCR-A/B, EAN-8, EAN-13, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, POSTNET
<b>Consumables</b>	Ribbon: 9 million characters
<b>Standard Paper Handling</b>	Pushtractor and friction
<b>Optional Paper Handling</b>	Roll holder
<b>Number of Copies</b>	1 original + 4 copies
<b>Paper Type</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper Weight</b>	52 - 100 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 95 to 267 mm, 9.75 to 10.5 in, Length: 114 to 362 mm, 4.5 to 14.25 in. (Cut sheet); 114 to 558 mm (4.5 to 22.0 in) (Fanfold)
<b>Physical Weight</b>	5 kg, 11 lbs
<b>Physical Size</b>	369 x 283 x 130 mm, 14.5 x 11.1 x 5.1 in., (W x D x H)
<b>Acoustics</b>	57 dB(A)
<b>Power Voltage</b>	100-240 V - 50/60 Hz
<b>Power Consumption</b>	less than 1.2 Watt Sleep Mode
<b>Temperature</b>	+5° to +35° C; 41° to 95° F 10% to 80% humidity
<b>Workload</b>	6,000 pages per month
<b>MTBF</b>	12,000 hours
<b>Drivers</b>	Windows Vista/7/ 8.1 and Server 2008/2012
<b>Cover Set Color</b>	Night Sky Gray (Pantone 432)
<b>Warranty</b>	One year return to depot

**Note:** For OCR applications, it is recommended that your readers are tested with sample printouts supplied by Dascom. Paper is a highly variable medium and should be tested prior to purchase.

Dascom Americas  
 34 Lakeview Court  
 Verona, VA 24482  
 Tel: 540-904-0391 or 877-434-1377  
 Fax: 540-242-7221  
 www.dascomamericas.com

SERIAL MATRIX PRINTERS   
 MOBILE PRINTERS   
 FLATBED PRINTERS   
 THERMAL PRINTERS 