

## Tally DASCOM LA2820: Peak performance



The LA2820 printer is meticulously designed for peak performance. DASCOM'S fastest matrix forms printer offers exceptional print speeds, throughput, and workload capability for heavy operation in demanding environments.

An excellent value, the LA2810 offers low operation costs and is well matched to DEC environments. Dual friction paper handling means forms are easy to feed and print, while a metal tear bar limits the chance of wasted forms.

The printer is designed for automated operation so

### Common Applications:

- Warehouse environments
- Manufacturing
- Trucking & Logistics
- Retail
- Other industrial environments

## Highlights at a glance:

- Print up to 1200 characters per second at 12 CPI
- Rated workload 50,000 printed pages per month
- Long-life print head rated at 750 million characters
- DEC Emulation
- Ethernet interface with IPv6 support
- Print up to 6 copies (original + 5)
- Metal tear-off edge for no wasted forms
- Low decibel quiet operation
- Industrial design for demanding environments

user intervention is minimized, and menu settings can even be saved via the USB host interface or new firmware can be uploaded easily.

A backlit display means all information can be read easily. Also, a browser-based Tally DASCOM Web Panel is available for network management.

Equipped with an Ethernet interface with IPv6 support and a USB interface as standard, the printer can also be upgraded with serial/parallel interface thus making it flexible and easy to integrate into many systems.

# Tally DASCOM LA2820: Peak performance

Print speed	1200 cps (Fastest Draft); 800 cps (Draft), 267 cps (NLQ) at 12 cpi
Resolution	Up to 360 x 360 dpi (ESC/P Emulation only)
Throughput	690 pages per hour (ECMA 132 @ 10cpi)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million characters
Standard Memory	256 kB
Standard Connectivity	USB 2.0 (Full Speed) and Ethernet 10/100 Base T with Ipv6 support. USB host
Optional Connectivity	Ethernet with IPDS
Standard Emulation	DEC PPL2, IBM Proprinter XL24e, EPSON LQ ESC P/2
Fonts	Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing
Consumables	Ribbon: 20 million characters
Administration	Backlit Panel, internal web page,
Standard Paper Handling	Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling
Optional Paper Handling	Additional Push Tractor (front), Automatic Cutting Device
Number of Copies	Push Tractor (Front) 1 original + 5 copies
Paper Type	Continuous Forms, Multi-Part Forms (.025" thick max.)
Paper Weight	60 - 120 g/m <sup>2</sup>
Paper Size	Width: 3" to 16.5" (76 mm - 419 mm) Length: 3" to 22" (76 mm - 560 mm)
Physical Size (W x D x H)	24.5" x 17" x 11" (624 x 432 x 280 mm)
Physical Weight	42 lbs (Approximately 19 kg)
Acoustic	54 dB(A)
Power Voltage	120 V or 230 V (auto-switching)
Power Consumption	75 Watt while Printing; 2 Watts power save
Workload	Up to 50,000 pages per month
Drivers	Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP
Reliability MTBF	20.000 hours
Temperature and Humidity	50 °F - 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing)
Warranty	90 days on-site warranty
Options	2nd tractor, Print stand, Automatic Cut Device

**DASCOM Americas**  
 34 Lakeview Court  
 Verona, Virginia, 24482 . USA.  
 Tel: +1 (877) 434-1377  
[www.dascomamericas.com](http://www.dascomamericas.com)  
[info.us@dascom.com](mailto:info.us@dascom.com)

**DASCOM Europe GmbH**  
 Heuweg 3 | 89079 Ulm | GERMANY  
 Tel.: +49 731 2075-0  
 Fax: +49 731 2075-100  
[info@dascom.com](mailto:info@dascom.com)  
[www.dascomeurope.de](http://www.dascomeurope.de)

**DASCOM (Holdings) LTD.**  
 R. 1811-1816A | Nan Fung Centre  
 264-298 Castle Peak Road  
 Tuen Wan, N. T. | Hong Kong  
 Tel.: +852 2498 1507  
 Fax: +852 2413 6047