

## T2150, T2150S



*Tally*

The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price – everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the T2150S features a cutting device which separates forms automatically.

### Highlights at a glance:

- Print speeds up to 900 cps
- 26,000 pages per month workload
- 80 columns
- 24 pin print head produces excellent print quality
- Automatic gap adjustment and quick tear
- Straight through paper path for easy forms loading
- Parallel and Serial interfaces standard
- LAN, IBM AS400/iSeries, Mainframe optional

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

### Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Sample Intelligent Mail Barcode



Available Configuration:

- **T2150** Standard Product
- **T2150 IGP** with IGP/PJL support
- **T2150S** with Automatic Cutter
- **T2150S IGP** with Automatic Cutter and IGP/PJL support

## T2150, T2150S

<b>Print Speed</b>	720 cps (Fastest Draft), 600 cps (Draft), 270 cps (DPQ), 180 cps (NLQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Throughput (ECMA 132)</b>	482 pages per hour
<b>Character Density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	400 million characters
<b>Memory</b>	128 kB
<b>Standard Connectivity</b>	Parallel (Bi-directional) and Serial RS232
<b>Optional Connectivity</b>	Serial Current Loop (20mA), Ethernet 10/100BaseT
<b>Standard Emulations</b>	IBM ProPrinter XL24, Epson LQ2250, MTPL + Barcode + LCP
<b>Optional Emulations</b>	IGP Version: IGP/PGL, Code V, MT660, Printronix P6000, HP2564C DEC LA 75, ECMA 9011, Eastern Europe, MT50
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and Large Character Printing (LCP)
<b>Consumables</b>	Ribbon: 3,5 million characters
<b>Standard Paper Handling</b>	Push tractors with paper parking and automatic gap adjustment (AGA).
<b>Optional Paper Handling</b>	Additional push tractor, front. Additional push tractor, rear. Front single bin automatic sheet feeder. Paper cutting device (T2150S only)
<b>Number of Copies</b>	Push tractor front: 1 Original + 5 copies; Push tractor rear: 1 Original +1 copy; Single sheet: 1 Original + 5 copies
<b>Cutting Device</b>	only T2150S
<b>Paper Type</b>	Continuous forms, single sheets
<b>Paper Weight</b>	60-120 g/m <sup>2</sup>
<b>Paper Format</b>	Width: 3" to 10"; Length: 3" to 23"
<b>Physical Weight</b>	22 lbs
<b>Physical Size</b>	18.1" x 11.8" x 11.6" (W x D x H)
<b>Noise Level (ISO 7779)</b>	53 dB(A)
<b>Power Voltage</b>	120 V or 230 V (selectable)
<b>Power Consumption</b>	40 Watt printing; <10 W Sleep Mode
<b>Temperature</b>	+10° to +35° C; 20% to 80% humidity (not condensing)
<b>Print Volume</b>	26.000 pages per month
<b>MTBF</b>	10.000 hours
<b>Warranty</b>	1 year return to base
<b>Printer Drivers</b>	Windows 2000/XP/Vista/7; Windows Server 2003/2008