Tally DASCOM T2810



DASCOM®



Highlights at a glance:

- Print up to 960 characters per second at 12 CPI
- Rated workload 50,000 printed pages per month
- Long-life print head rated at 750 million characters
- Ethernet interface with IPv6 support (standard)
- Variety of optional interfaces
- Print up to 7 copies (original + 6)
- Metal tear-off edge for no wasted forms
- Industrial design for demanding environments

The 2810 printer is designed for fast, efficient performance under the most rigorous conditions in challenging environments. Built to perform, the 2810 gives users exceptional forms handling, the ability to print heavy workloads, and rugged durability that ensures quality operation in tough conditions.

An excellent value, the 2810 offers low

operation costs and is well-matched to Microsoft® Windows applications. It is also highly compatible with other host operation environments including legacy systems.

As intuitive as it is tough, the 2810 is also easy to use and its automated features limit the potential for human error during operation.

Common Applications:

Warehouse environments Manufacturing Trucking & Logistics Retail Other industrial environments



Tally DASCOM T2810

| Print speed | 960 cps (Fastest Draft); 800 cps (Draft), 267 cps (NLQ) at 12 cpi |
|---------------------------|---|
| Resolution | Up to 360 x 360 dpi (ESC/P Emulation only) |
| Throughput | 640 pages per hour (ECMA 132 @ 10cpi) |
| Character Density | 5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi |
| Line Density | 2, 3, 4, 6, 8, 12 lpi |
| Printhead Life | 750 million characters |
| Standard Memory | 256 kB |
| Standard Connectivity | USB 2.0 (Full Speed) and Ethernet 10/100 Base T with Ipv6 support. USB host |
| Optional Connectivity | Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS |
| Standard Emulation | IBM Proprinter XL24e, Epson LQ2550, EPSON LQ2170 (ESC P/2), MTPL, Genicom ANSI + Barcodes + LCP |
| Fonts | Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing |
| Consumables | Ribbon: 20 million characters |
| Administration | Backlit Pannel, internal web page, |
| Standard Paper Handling | Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling |
| Optional Paper Handling | Additional Push Tractor (front), Automatic Cutting Device |
| Number of Copies | Push Tractor (Front) 1 original + 6 copies |
| Paper Type | Continuous Forms, Multi-Part Forms (.025" thick max.) |
| Paper Weight | 60 - 120 g/m² |
| Paper Size | Width: 3" to 16.5" (76 mm - 419 mm) Length: 3" to 22" (76 mm - 560 mm) |
| Physical Size (W x D x H) | 24.5" x 17" x 11" (624 x 432 x 280 mm) |
| Physical Weight | 42 lbs (Approximately 19 kg) |
| Acoustic | 54 dB(A) |
| Power Voltage | 120 V or 230 V (auto-switching) |
| Power Consumption | 75 Watt while Printing; 2 Watts power save |
| Workload | Up to 50,000 pages per month |
| Drivers | Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP |
| Reliability MTBF | 20.000 hours |
| Temperature and Humidity | 50 °F - 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) |
| Warranty | 90 days on-site warranty |
| Options | Cutting device, pedestal, 2nd tractor |

DASCOM Americas

34 Lakeview Court Verona, Virginia, 24482. USA. Tel: +1 (877) 434-1377 www.dascomamericas.com info.us@dascom.com

DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY Tel.: +49 731 2075-0 Fax: +49 731 2075-100 info@dascom.com www.dascomeurope.de

DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre 264-298 Castle Peak Road Tuen Wan, N. T. | Hong Kong Tel.: +852 2498 1507

Fax: +852 2413 6047

May 2024 Ver iD.02