

Tally DASCOM T2810





Highlights at a glance:

- Print up to 960 characters per second at 12 CPI
- Rated workload 50,000 printed pages per month
- Long-life print head rated at 750 million charac-
- Ethernet interface with IPv6 support (standard)
- Variety of optional interfaces
- Print up to 7 copies (original + 6)
- Metal tear-off edge for no wasted forms
- Industrial design for demanding environments

The 2810 printer is designed for fast, efficient performance under the most rigorous conditions in challenging environments. Built to perform, the 2810 gives users exceptional forms handling, the ability to print heavy workloads, and rugged durability that ensures quality operation in tough conditions.

An excellent value, the 2810 offers low

operation costs and is well-matched to Microsoft® Windows applications. It is also highly compatible with other host operation environments including legacy systems.

As intuitive as it is tough, the 2810 is also easy to use and its automated features limit the potential for human error during operation.

Common Applications:

Warehouse environments Manufacturing **Trucking & Logistics** Retail Other industrial environments



Tally DASCOM T2810

Character Density Line	Print speed	960 cps (Fastest Draft); 800 cps (Draft), 267 cps (NLQ) at 12 cpi
Character Density 5, 6, 7, 5, 8, 6, 10, 12, 15, 17.1, 20 cpi Line Density 2, 3, 4, 6, 8, 12 lpi Printhead Life 750 million characters Standard Memory 256 kB Standard Connectivity USB 2.0 [Full Speed] and Ethernet 10/100 Base T with Ipv6 support. USB host Optional Connectivity Parallel EEE 1285 and RS-232 Serial combo interface, Ethernet with IPVS Standard Emulation IBM Proprinter XL24e, Epson L02550, EPSON L02170 (ESC P/2), MTPL, Genicom ANSI+ Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souwenir, DCR-A/S, 17 Barcodes and Large Character Printing Consumables Ribbor. 20 million characters Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Teacr off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (front) and Push Tractor (front) and Indignate Cutting Device Paper Type Continuous Forms, Multi-Part Forms (025° thick max.) Paper Weight General Printing 2 Weight Physical Size (W x D x H) 42 lbs (Approximately 19 kg) Acco	Resolution	Up to 360 x 360 dpi (ESC/P Emulation only)
Line Density 2, 3, 4, 6, 8, 12 lpi Printhead Life 750 million characters Standard Memory 256 kB Standard Connectivity USB 2.0 (Full Speed) and Ethernet 10/100 Base T with IpoS support. USB host Optional Connectivity Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS Standard Emulation IBM Proprinter XL24e, Epson L02550, EPSON L02170 (ESC P/2), MTPL, Genicom ANSI+ Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing Consumables Ribbors. 20 million characters Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push If a Copies Push If a Copies Push If a Copies Push If a Copies Push If Parallel Pu	Throughput	640 pages per hour (ECMA 132 @ 10cpi)
Printhead Life 750 million characters Standard Memory 256 kB Standard Memory 256 kB Standard Connectivity USB 2.0 (Full Speed) and Ethernet 10/100 Base T with Ipv6 support. USB host Optional Connectivity Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS Standard Emulation IBM Proprinter XL24e, Epson L02550, EPSON L02170 (ESC P/2), MTPL, Genicom ANSI + Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, ORF-A/B, 17 Barcodes Consumables Ribbon: 20 million characters Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (front) 1 original + 6 copies Paper Nype Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 - 120 g/m² Paper Size Width: 3" to 165" (76 mm - 419 mm) Physical Weight 42 (bs (Approximately 19 kg) Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 90 days on-site warranty	Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Standard Memory 256 kB Standard Connectivity USB 2.0 (Full Speed) and Ethernet 10/100 Base T with Ipv6 support. USB host Optional Connectivity Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS Standard Emulation IBM Proprinter XL24e, Epson L02550, PSON L02170 (ESC P/2), MTPL, Genicom AMSI + Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Bercodes Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 - 120 g/m² Paper Size Violth 3" to 165" (76 mm - 419 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts powers and Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Beliability MTBF 2,000 hours Temperature and Humidity 90 days on-site warranty	Line Density	2, 3, 4, 6, 8, 12 lpi
Standard Connectivity USB 2.0 (Full Speed) and Ethernet 10/100 Base T with (pv6 support. USB host Optional Connectivity Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS Standard Emulation IBM Proprinter XL24e, Epson L02550, EPSON L02170 (ESC P/2), MTPL, Genicom ANSI + Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes Ribbors 20 million characters Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) 1 original + 6 copies Paper Type Continuous Forms, Multi-Part Forms (025" thick max.) Paper Weight Continuous Forms, Multi-Part Forms (025" thick max.) Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 500 mm) Physical Size (W x D x H) Physical Size (W x D x H) Physical Weight Acoustic Standard Power Voltage Power Voltage Power Voltage Power Consumption To St Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Quond hours Temperature and Humidity Podays on-site warranty	Printhead Life	750 million characters
Optional Connectivity Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS Standard Emulation IBM Proprinter XL24e, Epson L02550, EPSON L02170 (ESC P/Z), MTPL, Genicom ANSI + Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, DCR-A/B, 17 Barcodes and Large Character Printing Consumables Ribbon. 20 million characters Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (Front), Automatic Cutting Device Number of Copies Push Tractor (Front) and Proprinter Cutting Device Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42.5" x 17" x 11" (624 x 432 x 280 mm) Power Voltage 120 V or 230 V (auto-switching) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload <td>Standard Memory</td> <td>256 kB</td>	Standard Memory	256 kB
Standard Emulation IBM Proprinter XL24e, Epson LO2550, EPSON LO2170 (ESC P/2), MTPL, Genicom ANSI + Barcodes + LCP Fonts Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing Consumables Ribbon: 20 million character Printing Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) original + 6 copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Wight: 3" to 16,5" (76 mm – 419 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 90 days on-site warranty	Standard Connectivity	USB 2.0 (Full Speed) and Ethernet 10/100 Base T with lpv6 support. USB host
Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-AVB, 17 Barcodes and Large Character Printing Consumables Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (Front). Automatic Cutting Device Number of Copies Push Tractor (Front) and Park Forms (J025" thick max.) Paper Type Continuous Forms, Multi-Part Forms (J025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 550 mm) Physical Size (W x D x H) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dg(A) Power Voltage 120 V or 230 V (autor-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 90 days on-site warranty	Optional Connectivity	Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS
Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) and Park position, Dual friction for better paper handling Additional Push Tractor (Front), Automatic Cutting Device Number of Copies Push Tractor (Front) and Park position, Dual friction for better paper handling Additional Push Tractor (Front), Automatic Cutting Device Number of Copies Push Tractor (Front) and Push Tractor (Front) and Park position, Dual friction for better paper handling Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) and Park position, Dual friction for better paper handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Front) 1 original + 6 copies Paper Handling Optional Push Tractor (Fr	Standard Emulation	IBM Proprinter XL24e, Epson LQ2550, EPSON LQ2170 (ESC P/2), MTPL, Genicom ANSI + Barcodes + LCP
Administration Backlit Pannel, internal web page, Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) 1 original + 6 copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dkg/. Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20,000 hours Temperature and Humidity 90 days on-site warranty	Fonts	Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing
Standard Paper Handling Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) 1 original + 6 copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20,000 hours Temperature and Humidity 90 days on-site warranty	Consumables	Ribbon: 20 million characters
Optional Paper Handling Optional Paper Handling Additional Push Tractor (front), Automatic Cutting Device Number of Copies Push Tractor (Front) 1 original + 6 copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm) Physical Size (W x D x H) 24.5" x 17" x 11" (624 x 432 x 280 mm) Physical Weight 42 lbs (Approximately 19 kg) Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Reliability MTBF 20,000 hours Temperature and Humidity 90 days on-site warranty	Administration	Backlit Pannel, internal web page,
Number of Copies Paper Type Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm) Physical Size (W x D x H) Physical Size (W x D x H) Physical Weight Acoustic Power Voltage Power Voltage Power Consumption Privers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Temperature and Humidity Warranty Push Tractor (Front) 1 original + 6 copies Popies Continuous Forms, Multi-Part Forms (.025" thick max.) 60 – 120 g/m² Con + 120 g/m² Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Power Voltage Power Volta	Standard Paper Handling	
Paper Type Paper Weight Continuous Forms, Multi-Part Forms (.025" thick max.) Paper Weight 60 – 120 g/m² Paper Size Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm) Physical Size (W x D x H) Physical Size (W x D x H) Physical Weight Acoustic 54 dB(A) Power Voltage Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Z0.000 hours Temperature and Humidity 90 days on-site warranty	Optional Paper Handling	Additional Push Tractor (front), Automatic Cutting Device
Paper Weight Paper Size Paper Size Width: 3" to 16.5" (76 mm - 419 mm) Length: 3" to 22" (76 mm - 419 mm) Physical Size (W x D x H) Physical Size (W x D x H) Physical Weight Acoustic State (W x D x H) Power Voltage Power Consumption Power Consumption To Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Remperature and Humidity So "F - 95" (+10 "C to +35" C), 15% to 75% RH (not condensing) Warranty So Saper Size Windows 8/10 (32 and 54 bits) and Server 2012/2016; SAP Reliability MTBF So Sp Sp (+10 "C to +35" C), 15% to 75% RH (not condensing)	Number of Copies	Push Tractor (Front) 1 original + 6 copies
Paper Size Width: 3" to 16.5" (76 mm - 419 mm) Length: 3" to 22" (76 mm - 560 mm) Physical Size (W x D x H) Physical Weight Acoustic Power Voltage Power Consumption Power Consumption Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF Temperature and Humidity Workload Width: 3" to 16.5" (76 mm - 419 mm) Length: 4	Paper Type	Continuous Forms, Multi-Part Forms (.025" thick max.)
Physical Size (W x D x H) Physical Size (W x D x H) Physical Weight Acoustic Fower Voltage Power Consumption Power Consumption Power Size (W x D x H) Drivers Reliability MTBF Temperature and Humidity Temperature Length: 3" to 22" (76 mm – 560 mm) 24.5" x 17" x 11" (624 x 432 x 280 mm) 24.5" x 17" x 11" (624 x 432 x 280 mm) 24.5" x 17" x 11" (624 x 432 x 280 mm) 24.5" x 17" x 11" (624 x 432 x 280 mm) 42.1bs (Approximately 19 kg) 42.1bs (Approximately 19 kg) 42.1bs (Approximately 19 kg) 43.2 d B(A) 44.2 lbs (Approximately 19 kg) 44.2 lbs (Approximately 19 kg) 45.2 d B(A) 46.2 Watts power save Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP 86.1ability MTBF 20.000 hours Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty	Paper Weight	$60 - 120 \text{ g/m}^2$
Physical Weight Acoustic 54 dB(A) Power Voltage Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F - 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty	Paper Size	Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm)
Acoustic 54 dB(A) Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Physical Size (W x D x H)	24.5" x 17" x 11" (624 x 432 x 280 mm)
Power Voltage 120 V or 230 V (auto-switching) Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Physical Weight	42 lbs (Approximately 19 kg)
Power Consumption 75 Watt while Printing; 2 Watts power save Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty	Acoustic	54 dB(A)
Workload Up to 50,000 pages per month Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Power Voltage	120 V or 230 V (auto-switching)
Drivers Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP Reliability MTBF 20.000 hours Temperature and Humidity 50 °F - 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Power Consumption	75 Watt while Printing; 2 Watts power save
Reliability MTBF Zo.000 hours Temperature and Humidity 50 °F - 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Workload	Up to 50,000 pages per month
Temperature and Humidity 50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing) Warranty 90 days on-site warranty	Drivers	Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP
Warranty 90 days on-site warranty	Reliability MTBF	20.000 hours
	Temperature and Humidity	50 °F – 95 °F (+10 °C to +35 °C), 15% to 75% RH (not condensing)
Options Cutting device, pedestal, 2nd tractor	Warranty	90 days on-site warranty
	Options	Cutting device, pedestal, 2nd tractor

DASCOM Americas

34 Lakeview Court Verona, Virginia, 24482 . USA. Tel: +1 (877) 434-1377 www.dascomamericas.com info.us@dascom.com

DASCOM Europe GmbH

Heuweg 3 | 89079 Uim | GERMANY Tel.: +49 731 2075-0 Fax: +49 731 2075-100 info@dascom.com www.dascomeurope.de

DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre 264-298 Castle Peak Road Tuen Wan, N. T. | Hong Kong Tel.: +852 2498 1507

Fax: +852 2413 6047

May 20224 Ver iD.02

Copyright © 2024 DASCOM Americas. All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.