

## New Tally 4347-i11 multiform printer



### Tally DASCOM 4347-i11: Lasting Impact. Built to Perform.

The Tally 4347-i11 printer is built for peak performance in extreme conditions. Designed specifically for the IBM® environment, the DASCOM'S 4347—i11 fastest matrix forms printer offers exceptional print speeds, throughput, and workload capability for heavy operation in demanding environments.

A variety of “human comfort” features make the 4347-i series printer easy to operate. Users enjoy a straight through paper path for easy forms loading and dual friction paper feeding means paper feed is accurate and predictable. A backlit panel means operations are efficiently carried out since users can easily read and perform controls. User intervention errors are minimized by the printer’s intuitive design.

- Print up to 1200 characters per second at 12 CPI
- Rated workload 50,000 printed pages per month
- Long-life print head rated at 750 million characters
- Ethernet interface with IPv6 support
- Print up to 6 copies (original + 5)
- Metal tear-off edge for no wasted forms

#### Typical Operating Environments

- Manufacturing
- Warehousing
- Retail
- Transportation
- Logistics

Industrial

## Tally 4347-i11 multiform printer

<b>Print speed</b>	1200 cps (Fastest Draft); 1000 cps (Draft), 333 cps (NLQ) at 12 cpi
<b>Resolution</b>	Up to 360 x 360 dpi (ESC/P Emulation only)
<b>Throughput</b>	690 pages per hour (ECMA 132 @ 10cpi)
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	750 million characters
<b>Standard Memory</b>	256 Kb
<b>Standard Connectivity</b>	USB 2.0 and Ethernet 10/100 Base T with Ipv6 support. USB host
<b>Optional Connectivity</b>	Parallel IEEE 1285 and RS-232 Serial combo interface, Ethernet with IPDS
<b>Standard Emulation</b>	IBM Proprinter XL24e, Epson LQ2550, EPSON LQ2170 (ESC P/2), MTPL, Gemicom ANSI + Barcodes + LCP
<b>Fonts</b>	Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 Barcodes and Large Character Printing
<b>Consumables</b>	Ribbon: 20 million characters
<b>Administration</b>	Backlit Panel, internal web page, System settings/firmware upload via USB host interface
<b>Standard Paper Handling</b>	Push Tractor for continuous paper with straight paper path, Tear off and Park position, Dual friction for better paper handling
<b>Optional Paper Handling</b>	Additional Push Tractor (front)
<b>Number of Copies</b>	Push Tractor (Front) 1 original + 5 copies
<b>Paper Type</b>	Continuous Forms, Multi-Part Forms (.025" thick max.)
<b>Paper Weight</b>	60 – 120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 3" to 16.5" (76 mm – 419 mm) Length: 3" to 22" (76 mm – 560 mm)
<b>Physical Size (W x D x H)</b>	24.5" x 17" x 11" (624 x 432 x 280 mm)
<b>Physical Weight</b>	45.6 lbs (Approximately 20.7 kg)
<b>Acoustic</b>	54 dB(A)
<b>Power Voltage</b>	120 V or 230 V (auto-switching)
<b>Power Consumption</b>	75 Watt while Printing; 2 Watts power save
<b>Workload</b>	Up to 50,000 pages per month
<b>Drivers</b>	Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP
<b>Reliability MTBF</b>	20,000 hours
<b>Temperature</b>	50 °F – 95 °F (+10 °C to +35 °C)
<b>Humidity</b>	15% to 75% RH (not condensing)
<b>Warranty</b>	One year on-site.
<b>Options</b>	2nd tractor, Print stand

### Tally 4347-i11 multiform printer