

T2365/T2365 HD



Tally

Highlights at a Glance :

- Up to 9 part forms
- Full range of automatic features to minimize user intervention.
- Ideal for 'On-Demand' and 'Batch' applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100BaseT) standard.
- Optional Interfaces: RS-232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems, including Windows, and legacy systems

The T2365 series printers represent top of the line print speeds, rugged durability and unsurpassed performance under the most extreme conditions. These work-horse printers guarantee crisp, dark, clear and legible print thanks to the advanced engineering of the 24 pin print head. This head is built for long life and a heavy workload so even in the most challenging operating environment, you can be assured of the best in quality and performance.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

These products are well matched to Microsoft Windows applications, and highly compatible with other host operating environments including legacy systems.

Fully automated operation, coupled with the 'straight' through paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Intelligent Mail Barcode - be sure your printer has this important feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Intelligent Mail Barcode sample



Available Configuration:

- | | |
|---------------|---|
| • T2365 | Standard Product |
| • T2365 2T | with additional Rear Tractor |
| • T2365 HD | Heavy Duty version for up to 9-parts |
| • T2365 2T HD | Heavy Duty version with additional Rear Tractor |

T2365/T2365 HD

Print Speed	900 cps (Fastest Draft); 640 cps (Draft), 180 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	605 pages per hour (HD 587 pages per hour)
Character Density	5,6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	500 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-directional) and Ethernet 10/1q00 BaseT
Optional Connectivity	RS-232 Serial, Ethernet with SCS or IPDS, Coax/Twinax with SCS or IPDS
Standard Emulation	IBM ProPrinter XL24, Epson LQ (ESC P/2), MTPL + Barcode + LCP
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564C, ANSI
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable LCP
Consumables	Ribbon: 20 million characters
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 5 copies or 1 original + 8 copies (HD version only) Push tractor rear: 1 original + 3 copies (2T version)
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	42 lbs. (19 kg)
Physical Size	24.5" x 17" x 11" (W x D x H)
Acoustic	59 dB(A)
Power Voltage	120 (V) or 230 (V) (auto-switching)
Power Consumption	60 (W) Printing; 18 (W) Power Save
Temperature	+50 to +95 F; 20% to 80% humidity (not condensing)
Workload	48,000 pages per month
MTBF	12,500 hours
Warranty	90 days On-Site Warranty
Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008/2012; SAP

Note

For OCR applications it is recommended that your readers are tested. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM Americas Corporation

34 Lakeview Court
Verona, Virginia USA 24482
Tel: 877 434 1377
www.dascomamericas.com

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS